

C. Amendment to the Claims

Please cancel claims 4 and 5 without prejudice or disclaimer.

Please amend claims 1, 6, 8, 9, 13 and 17 as follows. A complete listing of the claims pending in this application is provided.

1. (Currently Amended) An image forming apparatus comprising:  
an image bearing member including a plurality of switching elements that are arranged in a moving direction and a generatrix direction of said image bearing member; and  
latent image forming means for forming a latent image on said image bearing member, said latent image forming means including a voltage generating means for generating a voltage in each switching element in accordance with an image signal,  
wherein each switching element corresponds to one dot of pixels of the latent image, and  
wherein a peripheral length of said image bearing member in the moving direction is an integral multiple of the dot.

2. (Original) An image forming apparatus according to claim 1,  
wherein each switching element includes electrodes and at least one of said electrodes is formed using an organic semiconductor.

3. (Original) An image forming apparatus according to claim 1,  
wherein said image bearing member has a drum shape.

4-5. (Cancelled)

6. (Currently Amended) An image forming apparatus comprising:  
an image bearing member including a plurality of switching elements that  
are arranged in a moving direction and a generatrix direction of said image bearing  
member;

latent image forming means for forming a latent image on said image  
bearing member, said latent image forming means including a voltage generating means for  
generating a voltage in each switching element in accordance with an image signal; and  
according to claim 1, further comprising

optical communications means for inputting the image signal into each  
switching element.

7. (Original) An image forming apparatus according to claim 6,  
wherein said optical communications means includes:

a light-receiving unit that is provided in a non-image area of said image  
bearing member in which no image is formed; and

a light-emitting unit that irradiates said light-receiving unit with light.

8. (Currently Amended) An image forming apparatus comprising:

an image bearing member including a plurality of switching elements that are arranged in a moving direction and a generatrix direction of said image bearing member;

latent image forming means for forming a latent image on said image bearing member, said latent image forming means including a voltage generating means for generating a voltage in each switching element in accordance with an image signal; and  
according to claim 1, further comprising

radio wave communications means for inputting the image signal into each switching element.

9. (Currently Amended) An image forming apparatus according to claim 1, further comprising a developing apparatus that develops the latent image using a developer,

wherein said developing apparatus includes a developer carrying member that carries the developer to a developing position.

10. (Original) An image forming apparatus according to claim 9, wherein the developer is one-component developer including toner.

11. (Original) An image forming apparatus according to claim 9, wherein the developer is two-component developer including toner and carrier.

12. (Original) An image forming apparatus according to claim 9, wherein the developer is developer produced by dispersing toner in an insulation liquid.

13. (Currently Amended) An image forming apparatus comprising:  
an image bearing member including a plurality of switching elements that  
are arranged in a moving direction and a generatrix direction of said image bearing  
member;

latent image forming means for forming a latent image on said image  
bearing member, said latent image forming means including a voltage generating means for  
generating a voltage in each switching element in accordance with an image signal; and  
a developing apparatus that develops the latent image using a developer,  
wherein said developing apparatus includes a developer carrying member  
that carries the developer to a developing position,

wherein a toner image is formed on said image bearing member by said  
developer carrying member,[[;]]

wherein said image forming apparatus further comprises density detecting  
means for detecting a density of the toner image formed on said image bearing member,  
and

wherein a voltage applied to each switching element is set on the basis of a  
detection result of said density detecting means.

14. (Original) An image forming apparatus according to claim 9,  
wherein:  
a toner image is formed on said image bearing member by said developer  
carrying member;  
said image forming apparatus further comprises density detecting means for  
detecting a density of the toner image formed on said image bearing member; and  
a voltage applied to said developer carrying member is set on the basis of a  
detection result of said density detecting means.

15. (Original) An image forming apparatus according to claim 9, further  
comprising a plurality of image forming portions that each includes said image bearing  
member and said developing apparatus,  
wherein said plurality of developing apparatuses contain toner in different  
colors.

16. (Original) An image forming apparatus according to claim 1,  
further comprising transferring means for transferring a toner image formed on said image  
bearing member to an image receiving member,  
wherein each switching element generates heat during the transferring by  
said transferring means.

17. (Currently Amended) An image forming apparatus comprising:

an image bearing member including a plurality of switching elements that are arranged in a moving direction and a generatrix direction of said image bearing member; and

latent image forming means for forming a latent image on said image bearing member, said latent image forming means including a voltage generating means for generating a voltage in each switching element in accordance with an image signal according to claim 1,

wherein each switching element includes a plurality of electrodes, and

wherein an image forming electrode, out of said plurality of electrodes, which forms the latent image is provided so as to protrude outward in comparison with other electrodes. ...

18. (Original) An image forming apparatus according to claim 17, wherein when a length of a portion of said image forming electrode that protrudes in comparison with other electrodes is referred to as L, a cross-sectional area of a pixel of the latent image in a direction along a surface of said image bearing member is referred to as S1, a density of the pixel is referred to as D, and a cross-sectional area of said image forming electrode in the direction along the surface of said image bearing member is referred to as S2, the following relation exists among S1, D, and S2

$$L \geq S1 \times D / S2.$$

19. (Original) An image forming apparatus according to claim 17,  
further comprising a conductive shield that covers each switching element,  
wherein said shield includes an opening portion corresponding to said image  
forming electrode so that said image forming electrode is exposed.

20. (Original) An image forming apparatus according to claim 19,  
wherein said conductive shield and said image forming electrode are covered with an  
insulating member.